



公差/General Tolerances(mm)	
0	>3
~	>6
3	>10
~	>18
6	>30
~	>50
10	>80
~	>120
18	>180
~	>250
30	>315
~	>500
50	>500
~	>1000
80	>1000
~	>1500
120	>1500
~	>2000
180	>2000
~	>2500
250	>2500
~	>3000
315	>3000
~	>4000
400	>4000
~	>5000
500	>5000
~	>6000
600	>6000
~	>8000
800	>8000
~	>10000
1000	>10000

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cover	PC	UL94V-2
3	Screw	Steel	M3/Ni Plated
2	Pin header	Copper alloy	M3/Sn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:		B	C	D
额定电压/Rated Voltage(V)/Current(A)		300/15	150/15	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级				
级/ Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		300/24	300/24	600/24
额定脉冲电压/Rate Impulse Voltage(KV)		5	5	5
额定扭矩/Torque Tightening(N·m/Lb·in)		M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG)		22~14		
间距/Pitch(mm)/线数范围/Poles		7.62/N=02~24P		
剥线长度/Stripping length(mm)		7		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

MATERIAL: /
 MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /
DEGSON 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD
 NAME: DG28C-A-XXP-1Y-00A(H)
 DRAWING NO.: DG28C-C01
 DRAFT: CenMZ 2020.05.29

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 1.5:1	REV	TO