



Pitch Range In mm	Nominal Dimension Range In mm					Tolerance
	Over 6	Over 10	Over 10	Over 30	Over 60	
T0	10	10	T0	30	60	Over 100
6	10	24	30	60	100	Over 150
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00
						±1.30
						±2*

ITEM	NAME OF PART	MATERIAL	NOTES
4	Nut	Copper Alloy	/
3	Current carrier	Copper Alloy	Sn Plated
2	Screw	Steel	Ni Plated
1	Housing	PC	UL94V-0

UL 标准/UL Standard: B C D  
 额定电压/电压/Rated Voltage(V)/Current(A) 600/120/600/120/600/5  
 额定扭矩/Torque Tightening(N·m/Lb.in) M6, 2.5/22.15  
 线径范围(线径)/Wire Range(flexible)(AWG) 20~2  
 间距/Pitch(mm)/线数范围/Poles 28.00/03P  
 剥线长度/Stripping length(mm) 18  
 使用温度范围/Operating temperature(°C) -40~+125  
 符合RoHS环保要求/Conform to RoHS Yes

MATERIAL: /  
 SURFACE: /

MAT NO.: /  
 STATUS: /

APPD: /  
 CHKD: /

DRFT: LY 2019.01.25  
 DRAWING NO.: DG32-A-C01  
 NAME: **DEGSON**® NINGBO DEGSON ELECTRICAL CO., LTD  
 宁波高松电子有限公司

TYPE: CUSTOMER DRAWING  
 SCALE: 1:1  
 SHEET: 1/1

REV	ECN	DESCRIPTION	DRFT	DATE